Atrust







- Dual Micro HDMI Display Ports
- Optimized for HDX
- Skype for Business Optimization
- Citrix HDX Ready Certified
- Power Button

4 Audio Out

- **6** Kensington Lock Slot
- 2 DC IN
- **6** USB 2.0 Port x 2
- Micro HDMI Port x 2

- **1** USB 3.0 Port x 2
- **8** LAN Port

- Integrated with Atrust Device Manager software
- Broadcom BCM2711B0 Quad Core 1.5GHz 64-bit CPU
- Support for WiFi and Bluetooth 5.0 BLE
- Low Power Consumption



Processor	Broadcom BCM2711B0 Quad Core 1.5GHz 64-bit CPU
System memory	2GB
Flash memory	16GB
Maximum resolution	Dual Display: Up to 3840 x 2160 @ 30 Hz Up to 2560 x 1600 @ 60 Hz
	Single Display: Up to 3840 x 2160 @ 60 Hz
Ethernet	Gigabit ethernet
WiFi	802.11b/g/n/ac wireless LAN
Bluetooth	Bluetooth 5.0 BLE
Dimensions	(W) 105.3 x (D) 76 x (H) 33.2 mm
Software	
Operating system	Atrust OS
Management	Atrust Device Manager (ADM) / Atrust Client Setup (ACS)
Protocol	Citrix® ICA/HDX™, Microsoft® RDP™ with RemoteFX™, VMware® Horizon View™ (PCoIP/RDP/Blast Extreme)
Manufacturing option	VESA Mount